DOUCET

MRS - GROOVER AND RIP SAW


For applications where close tolerances grooving on top or bottom with simultaneously ripping are the primary requirements. The MRS Groover and Rip Saw has been designed to control groove depth and lateral position, with high consistency and repeatability.



WARRANTY 1 YEAR



MRS - SIDE VIEW



MRS - SPINDLE ADJUSTMENT ACCESS



MRS - SPINDLES

CHARACTERISTICS & OPERATION

- Independent top or bottom spindles - self-powered, independently adjustable spindles which can be mounted on the top or bottom of the saw pass line;
- Manual spindle adjustment with digital electronic readouts for spindle height and lateral positioning;
- Feed systems available with a feed roller design, lug chain for squaring long parts or padded chain for non-marring requirements;
- Hold-down device to ensure proper groove depth;
- Capability to groove on top or bottom during the same passage through the cutting tools.

OPTIONS & SPECIFICATIONS

- According to customer's applications, the sawing width capacity is up to 10', allowing to groove across full width up to 5' x 10' sheet;
- Destacking and stacking systems can be combined for fully automated line when feeding thin panels;
- Brush cleaner with dust collectors following the saw chamber area;
- Hogger units on each side of panel when final sizing is required.

DOUCET
P. 1-866-673-8876
P. 1-819-367-2633
E. info@doucetinc.com
doucetinc.com

DISCOVER OUR RESOURCE CENTER

- Articles
- Tutorials
- Videos
- Technical Support
- Tools